


1. IDENTIFICATION

PRODUCT NAME	Rugged Ac55 HT
APPLICATION	Coating
USES ADVISED AGAINST	No specific uses advised against are identified.
SUPPLIER IDENTIFICATION	Rugged Coatings 2720 Southeastern Cir Birmingham, AL 35215
EMERGENCY TELEPHONE	(205) 440-4996

2. HAZARD(S) IDENTIFICATION

OSHA REGULATORY STATUS	This Product is Hazardous under the OSHA Hazard Communication Standard
PHYSICAL HAZARDS	Not Classified
HEALTH HAZARDS	Carc. 1A - H350
LABEL ELEMENTS	
PICTOGRAM	
SIGNAL WORD	Danger
HAZARD STATEMENTS	H350 Carc. 1Ar
PRECAUTIONARY STATEMENTS	<p>P201 Obtain special instructions before use.</p> <p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P308+P313 If exposed or concerned: Get medical advice/ attention.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with regulations.</p>
CONTAINS	Titanium Dioxide, Quartz (SiO ₂), Biocide - withheld as TRADE SECRET
OTHER HAZARDS	This product does not contain any substances classified as PBT or vPvB.

3. COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURES	
Limestone	10 - <50%
CAS number: 1317-65-3	
Titanium Dioxide	1 - <15%
CAS number: 13463-67-7	
Zinc oxide	0 - <5%

CAS number: 1314-13-2

Aluminum hydroxide 0 - <15%

CAS number: 21645-51-2

Quartz (SiO₂) <1%

CAS number: 14808-60-7

Ammonia <1%

CAS number: 1336-21-6

Biocide - withheld as TRADE SECRET <1%

CAS number: Proprietary

Kaolin <1%

CAS number: 1332-58-7

COMPOSITION COMMENTS

The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200. The product identifiers are withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. FIRST-AID MEASURES

GENERAL INFO	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
INHALATION	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
INGESTION	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical attention if symptoms are severe or persist.
SKIN CONTACT	Rinse with water.
EYE CONTACT	Rinse immediately with plenty of water. Do not rub eye. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Get medical attention if

any discomfort continues.

4. FIRST-AID MEASURES cont'd

PROTECTION OF FIRST AIDERS	First aid personnel should wear appropriate protective equipment during any rescue. Most important symptoms and effects, both acute and delayed
GENERAL INFO	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
INHALATION	Prolonged inhalation of high concentrations may damage respiratory system. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
INGESTION	Gastrointestinal symptoms, including upset stomach. Nausea, vomiting. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
SKIN CONTACT	Redness. Irritating to skin. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
EYE CONTACT	May cause temporary eye irritation.
NOTES TO PHYSICIAN	Treat symptomatically

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing	Do not use water jet as an extinguisher, as this will spread the fire. media

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

ADVICE FOR FIREFIGHTERS

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate for firefighters protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.
----------------------	---

ENVIRONMENTAL PRECAUTIONS

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil
---------------------------	---

or air).

6. ACCIDENTAL RELEASE MEASURES cont'd

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Methods for cleaning up	<p>Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind.</p> <p>SMALL SPILLAGES: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container.</p> <p>LARGE SPILLAGES: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water.</p> <p>Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.</p>
Reference to other sections	<p>For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.</p>

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING USAGE PRECAUTIONS

Usage Precautions	<p>Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists.</p> <p>May cause cancer. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.</p>
Advice on general occupational hygiene	<p>Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.</p>

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage precautions	<p>Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.</p>
Storage class	Miscellaneous hazardous material storage.
Shelf-Life	12 months
Storage Temperature (Min- Max)	1 °C (33.8 °F) - 49 °C (120.2 °F)

SPECIFIC END USES(S)

Specific end use(s)	The identified uses for this product are detailed in Section 1.
---------------------	---

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS OCCUPATIONAL EXPOSURE LIMITS

Comments The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known

LIMESTONE	Long-term exposure limit (8-hour TWA): OSHA 5 mg/m3	respirable fraction	
	Long-term exposure limit (8-hour TWA): OSHA 15 mg/m3	total dust	
TITANIUM DIOXIDE	Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m3		A4
	Long-term exposure limit (8-hour TWA): OSHA 15 mg/m3	total dust	
ZINC OXIDE	Long-term exposure limit (8-hour TWA): OSHA 5 mg/m3	fume	
	Long-term exposure limit (8-hour TWA): OSHA 15 mg/m3	total dust	
	Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m3	respirable fraction	
	Short-term exposure limit (15-minute): ACGIH 10 mg/m3	respirable fraction	
	Long-term exposure limit (8-hour TWA): OSHA 5 mg/m3	respirable fraction	
ALUMINUM HYDROXIDE	Long-term exposure limit (8-hour TWA): ACGIH 1 mg/m3		A4
QUARTZ (SiO2)	Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m3	respirable fraction	A2
AMMONIA	Long-term exposure limit (8-hour TWA): ACGIH 25 ppm 17 mg/m3		
	Short-term exposure limit (15-minute): ACGIH 35 ppm 24 mg/m3		
	Long-term exposure limit (8-hour TWA): OSHA 50 ppm 35 mg/m3		
BIOCIDE - withheld as TRADE SECRET	Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m3		A4
KAOLIN	Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m3		A4
	Long-term exposure limit (8-hour TWA): OSHA 5 mg/m3		
	Long term exposure limit (8-hour TWA): OSHA 15 mg/m3	total dust	

OSHA = Occupational Safety and Health Administration.
ACGIH = American Conference of Governmental Industrial Hygienists.
A4 = Not Classifiable as a Human Carcinogen.
A2 = Suspected Human Carcinogen.

TITANIUM DIOXIDE (CAS: 13463-67-7)	5000 mg/m3	IMMEDIATE DANGER TO LIFE AND HEALTH
ZINC OXIDE (CAS: 1314-13-2)	500 mg/m3	
SILICON DIOXIDE (CAS: 7631-86-9)	3000 mg/m3 3000 mg/m3	
QUARTZ (SiO2) (CAS: 14808-60-7)	50 mg/m3 25 mg/m3	
AMMONIA (CAS: 1336-21-6)	300 ppm	

PROTECTIVE EQUIPMENT



Appropriate engineering controls	Provide adequate ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. If inhalation hazards exist, a full-face respirator may be required instead.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION cont'd

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Color	Various colors
Odor	Mild. Amine
Odor threshold	Not available
pH	Not available
Melting point	0°C (as water)
Initial boiling point and range	100°C (boiling point of water)
Evaporation rate	Not available
Upper/lower flammability or explosive limits	Not available
Vapor pressure	17 mm Hg @ 20°C/68°F
Vapor density	Not available
Relative density	Not available
Specific Gravity	1.2 - 1.5
Partition coefficient	Not available
Auto-ignition temperature	Not available
Decomposition Temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidizing properties	Not available
Volatile organic compound	< 50 g/liter

10. STABILITY AND REACTIVITY

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.

Hazardous decomposition Does not decompose when used and stored as recommended. Thermal decomposition or products combustion products may include the following substances: Harmful gases or vapors.

11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS ACUTE TOXICITY - ORAL

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ACUTE TOXICITY - DERMAL

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ACUTE TOXICITY - INHALATION

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

SKIN CORROSION/IRRITATION

Skin corrosion/irritation Based on available data the classification criteria are not met.

SERIOUS EYE DAMAGE/IRRITATION

Serious eye damage/irritation Based on available data the classification criteria are not met.

RESPIRATORY SENSITIZATION

Respiratory sensitization Based on available data the classification criteria are not met.

SKIN SENSITIZATION

Skin sensitization Based on available data the classification criteria are not met. The product contains a small amount of sensitizing substance. May cause skin sensitization or allergic reactions in sensitive individuals.

GERM CELL MUTAGENICITY

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

CARCINOGENICITY

Carcinogenicity May cause cancer.

IARC carcinogenicity Contains a substance/a group of substances which may cause cancer. IARC Group 1 Carcinogenic to humans.

NTP carcinogenicity Contains: Silica, Crystalline (Respirable Size) Known human carcinogen.

REPRODUCTIVE TOXICITY

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity development Based on available data the classification criteria are not met.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

STOT - single exposure Not classified as a specific target organ toxicant after repeated exposure.

ASPIRATION HAZARD

Aspiration hazard Based on available data the classification criteria are not met.

General information May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

Skin Contact Prolonged contact may cause dryness of the skin. Discoloration of the skin.

Eye contact May cause temporary eye irritation.

Route of entry Ingestion Inhalation Skin and/or eye contact

Target Organs No specific target organs known

12. ECOLOGICAL INFORMATION

Toxicity	The product contains a substance which is very toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
----------	---

PERSISTENCE AND DEGRADABILITY

Persistence and degradability	The degradability of the product is not known.
-------------------------------	--

BIOACCUMULATIVE POTENTIAL

Bio-Accumulative Potential	No data available on bioaccumulation.
----------------------------	---------------------------------------

Partition coefficient	Not available
-----------------------	---------------

MOBILITY IN SOIL

Mobility	No data available
----------	-------------------

OTHER ADVERSE EFFECTS

Other adverse effects	None known
-----------------------	------------

13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. TRANSPORT INFORMATION

General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT)
UN NUMBER	Not applicable
UN PROPER SHIPPING NAME	Not applicable
TRANSPORT HAZARD CLASS(ES)	
DOT transport labels	No transport warning sign required
Transport labels	No transport warning sign required
PACKING GROUP	
Not applicable.	
ENVIRONMENTAL HAZARDS	
Environmentally Hazardous Substance	No
SPECIAL PRECAUTIONS FOR USER	Not applicable
DOT TIH Zone	Not applicable
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

15. OTHER INFORMATION

Classification abbreviations and acronyms	Carc. = Carcinogenicity
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision date	11/26/2021
Revision	2
Supersedes date	3/26/2021
SDS No.	
Hazard statements in full	H350 May cause cancer.
This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.	

16. REGULATORY INFORMATION

Regulatory References OSHA Hazard Communication Standard 29 CFR §1910.1200

US FEDERAL REGULATIONS

SARA Section 302 Extremely Hazardous

Substances Tier II Threshold

Planning Quantities None of the ingredients are listed or exempt.

CERCLA/SUPERFUND, HAZARDOUS SUBSTANCES/REPORTABLE QUANTITIES (EPA) The following ingredients are listed or exempt:

Ammonia Final CERCLA RQ: 1000(454) pounds (Kilograms) methyl

benzimidazol-2-yl carbamate Final CERCLA RQ: 10(4.54) pounds (Kilograms)

Biocide - withheld as TRADE SECRET Final CERCLA RQ: 100(45.4) pounds (Kilograms)

SARA Extremely Hazardous Substances

EPCRA Reportable Quantities None of the ingredients are listed or exempt.

SARA 313 EMISSION REPORTING The following ingredients are listed or exempt:

Ammonia 1.0 %

Zinc oxide 1.0 %

Biocide - withheld as TRADE SECRET 1.0 %

Biocide - withheld as TRADE SECRET 1.0 %

CAA ACCIDENTAL RELEASE PREVENTION None of the ingredients are listed or exempt.

FDA - Essential Chemical None of the ingredients are listed or exempt.

FDA - Precursor Chemical None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals None of the ingredients are listed or exempt.

US STATE REGULATIONS

CALIFORNIA PROPOSITION 65 CARCINOGENS AND REPRODUCTIVE TOXINS The following ingredients are listed or exempt:

Benzophenone Known to the State of California to cause cancer.

Silicon dioxide Known to the State of California to cause cancer.

Titanium Dioxide Known to the State of California to cause cancer.

Biocide - withheld as TRADE SECRET Known to the State of California to cause cancer.

CALIFORNIA AIR TOXICS "HOT SPOTS" (A-I)
The following ingredients are listed or exempt:

Silicon dioxide

Zinc oxide

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

CALIFORNIA DIRECTORS LIST OF HAZARDOUS SUBSTANCES
The following ingredients are listed or exempt:

Ammonia

Silicon dioxide

Zinc oxide

Biocide - withheld as TRADE SECRET

MASSACHUSETTS "RIGHT TO KNOW" LIST
The following ingredients are listed or exempt:

Ammonia

Limestone

Quartz (SiO₂)

Silicon dioxide

Titanium Dioxide

Zinc oxide

Biocide - withheld as TRADE SECRET Kaolin

16. REGULATORY INFORMATION cont'd

US STATE REGULATIONS

RHODE ISLAND "RIGHT TO KNOW" LIST

The following ingredients are listed or exempt:

Limestone

Quartz (SiO₂)

Titanium Dioxide

Zinc oxide

Propane-1,2-diol

Biocide - withheld as TRADE SECRET

Kaolin

MINNESOTA "RIGHT TO KNOW" LIST

The following ingredients are listed or exempt:

Benzophenone Limestone Quartz (SiO₂)

Silicon dioxide

Titanium Dioxide

Zinc oxide

Propane-1,2-diol

Biocide - withheld as TRADE SECRET

Kaolin

NEW JERSEY "RIGHT TO KNOW" LIST

The following ingredients are listed or exempt:

Ammonia

Limestone

Quartz (SiO₂)

Titanium Dioxide

Zinc oxide

Propane-1,2-diol

Biocide - withheld as TRADE SECRET

Methyl benzimidazol-2-yl carbamate

Biocide - withheld as TRADE SECRET

Kaolin

PENNSYLVANIA "RIGHT TO KNOW" LIST

The following ingredients are listed or exempt:

Ammonia

Limestone

Quartz (SiO₂)

Silicon dioxide

Titanium Dioxide

Zinc oxide

Propane-1,2-diol

Biocide - withheld as TRADE SECRET

Kaolin

INVENTORIES

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(B) EXPORT NOTIFICATION

The following ingredients are listed or exempt:

Benzophenone Note: Based on information provided by our suppliers, this product is considered "DRC Conflict Free" as defined by the SEC Conflict Minerals Final Rule (Release No. 34-67716; File No. S740-10; Date: 2012-08-22).