



MaAC

ACRYLIC SEAM SEALER

PRODUCT DESCRIPTION

Rugged Coatings MaAC is a tough, tenacious and durable white compound with high grade components. MaAC was developed and is designed to be a superior reflective material for new roofing, re-roofing, and roof maintenance markets. MaAC high pigment level provides superior hiding power, is highly reflective, easy to apply, and has superior hiding power. It has multiple application uses including laps, cracks, seams, directional wall changes, screw heads, and roof intrusions.

PACKAGING

SKU (White)	SIZE
ACRW-100-P	1 gallon pail
ACRW-100-P	2 gallon pail
ACRW-100-P	3.5 gallon pail
ACRW-100-P	5 gallon pail

COLOR



White

APPLICATION EQUIPMENT

MaAC can be applied by brush, roller or spray.

PRODUCT CHARACTERISTICS

Solids by Volume	42%
Solids by Weight	55%
Viscosity	Brush Grade
Tensile Strength	200+ psi
Elongation	200+%
VOC	<15 g/L
Clean Up	Mineral Spirits, Soap, paint thinner or water.

PRECAUTIONS

DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry. DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.





FOR PROFESSIONAL USE

PRE-TREATMENT

Treat all surfaces with the appropriate Rugged primer.

APPLICATION

Laps, cracks, seams, directional wall changes, screw heads, roof intrusions.

CURE

Cures by ultra violet rays; allow for sufficient daylight. Cure time affected by environmental conditions.

COVERAGE

Application rate at a minimum of 25-35 lineal feet per gallon with a 4-6" wide application at 1/8" thick.

CLEAN UP

Clean tools with mineral spirits, paint thinner, or soap and water.

WARRANTY AND DISCLAIMER

Rugged Coatings warrants MaAC to be free from defects in materials and manufacturing. Under this warranty, we will provide, at no charge, a quantity of Rugged Coatings MaAC sufficient to replace any Rugged Coatings MaAC proven to be defective when applied according to our written instructions and in applications recommended by us as suitable for the product. THIS LIMITED WARRANTY IS THE BUYER'S SOLE AND EXCLUSIVE REMEDY AGAINST RUGGED COATINGS REGARDING THE PRODUCT. IN NO EVENT SHALL RUGGED COATINGS BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, INDIRECT, PUNITIVE OR OTHER DAMAGES ARISING FROM THE USE OR PERFORMANCE OF THE PRODUCT.

Since methods of application and on site conditions can affect performance, RUGGED COATINGS MAKE NO OTHER WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE REGARDING THE PRODUCT, AND RUGGED COATINGS HEREBY DISCLAIM ALL SUCH OTHER WARRANTIES.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Rugged Coatings. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of the publication. Consult your Rugged Coatings Technical Representative to obtain the most recent Product Data Information.

If further information is needed, contact Rugged Coatings Technical Service at **205-440-4996**

