



MaAF

ACRYLIC MASTIC-FIBERED

205.440.4996
ruggedcoatings.com

3217 Messer Airport Hwy,
Birmingham, AL 35222

PRODUCT DESCRIPTION

Rugged Coatings MaAF is a fiber-fortified, durable, white elastomeric flashing compound developed to be a superior reflective material for new roofing, re-roofing, and roof maintenance markets. Easy to apply, fiber reinforced for superior crack-bridging performance. This reflective mastic is a superior choice in maintenance as well as new or re-roofing applications. This flexible mastic should be used at laps, cracks, seams, directional wall changes, screw heads, or any place a roof penetration is made. MaAF is available in four sizes: a 1-gallon pail (ACRW-100-P), 2-gallon pail (ACRW-100-P), 3.5-gallon pail (ACRW-100-P), 5-gallon pail (ACRW-100-P).

COVERAGE

Application rate at a minimum of 25-35 lineal feet per gallon with a 4-6" wide application at 1/8" thick.

APPLICATION

Laps, cracks, seams, directional wall changes, screw heads, roof intrusions.

PRODUCT CHARACTERISTICS

Solids by Weight	55%
Solids by Volume	42%
Viscosity	Trowel Grade
Tensile Strength	250psi
Elongation	100+ %
VOC	<15 g/L
Clean Up	Mineral Spirits, soap, paint thinner or water

COLORS

WHITE

PRE-TREATMENT

Treat all surfaces with the appropriate Rugged primer.

CURE

Cures by ultra violet rays; allow for sufficient daylight. Cure time affected by environmental conditions.

CLEAN UP

Clean tools with mineral spirits, paint thinner, or soap and water.

PRECAUTIONS

DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry. DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.

WARRANTY AND DISCLAIMER

Rugged Coatings warrants MaAF to be free from defects in materials and manufacturing. Under this warranty, we will provide, at no charge, a quantity of MaAF sufficient to replace any MaAF proven to be defective when applied according to our written instructions and in applications recommended by us as suitable for the product. THIS LIMITED WARRANTY IS THE BUYER'S SOLE AND EXCLUSIVE REMEDY AGAINST RUGGED COATINGS REGARDING THE PRODUCT. IN NO EVENT SHALL RUGGED COATINGS BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, INDIRECT, PUNITIVE OR OTHER DAMAGES ARISING FROM THE USE OR PERFORMANCE OF THE PRODUCT. Since methods of application and on site conditions can affect performance, RUGGED COATINGS MAKE NO OTHER WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE REGARDING THE PRODUCT, AND RUGGED COATINGS HEREBY DISCLAIM ALL SUCH OTHER WARRANTIES. The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Rugged Coatings. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of the publication. Consult your Rugged Coatings Technical Representative to obtain the most recent Product Data **Information**. If further information is needed, contact Rugged Coatings Technical Service at 205-440-4996.