



MaAC

ACRYLIC SEAM SEALER

205.440.4996
ruggedcoatings.com

3217 Messer Airport Hwy,
Birmingham, AL 35222

PRODUCT DESCRIPTION

Rugged Coatings MaAC is a tough, tenacious and durable white compound with high grade components. MaAC was developed and is designed to be a superior reflective material for new roofing, re-roofing, and roof maintenance markets. MaAC high pigment level provides superior hiding power, is highly reflective, easy to apply, and has superior hiding power. It has multiple application uses including laps, cracks, seams, directional wall changes, screw heads, and roof intrusions. MaAC is available in four sizes: a 1-gallon pail (ACRW-100-P), 2-gallon pail (ACRW-100-P), 3.5-gallon pail (ACRW-100-P), 5-gallon pail (ACRW-100-P).

GENERAL USES

As a finish coat in fluid applied roofing systems over metal, urethane foam, concrete, smooth BUR, asphalt and modified bitumen, granular cap sheets, single ply membranes, and other approved surfaces. Refer to Rugged Coatings Fluid Applied Roofing System Specifications.

APPLICATION

Laps, cracks, seams, directional wall changes, screw heads, roof intrusions.

PRODUCT CHARACTERISTICS

Solids by Weight	55%
Solids by Volume	42%
Viscosity	Brush Grade
Tensile Strength	200+ psi
Elongation	200+ %
VOC	<15 g/L
Clean Up	Mineral Spirits, soap, paint thinner or water

APPLICATION EQUIPMENT

MaAC can be applied by trowel and putty knife.

COLORS

WHITE

PRE-TREATMENT

Treat all surfaces with the appropriate Rugged primer.

CURE

Cures by ultra violet rays; allow for sufficient daylight. Cure time affected by environmental conditions.

CLEAN UP

Clean tools with mineral spirits, paint thinner, or soap and water.

PRECAUTIONS

DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry. DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.

WARRANTY AND DISCLAIMER

Rugged Coatings warrants MaAC to be free from defects in materials and manufacturing. Under this warranty, we will provide, at no charge, a quantity of MaAC sufficient to replace any MaAC proven to be defective when applied according to our written instructions and in applications recommended by us as suitable for the product. THIS LIMITED WARRANTY IS THE BUYER'S SOLE AND EXCLUSIVE REMEDY AGAINST RUGGED COATINGS REGARDING THE PRODUCT. IN NO EVENT SHALL RUGGED COATINGS BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, INDIRECT, PUNITIVE OR OTHER DAMAGES ARISING FROM THE USE OR PERFORMANCE OF THE PRODUCT. Since methods of application and on site conditions can affect performance, RUGGED COATINGS MAKE NO OTHER WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE REGARDING THE PRODUCT, AND RUGGED COATINGS HEREBY DISCLAIM ALL SUCH OTHER WARRANTIES. The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Rugged Coatings. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of the publication. Consult your Rugged Coatings Technical Representative to obtain the most recent Product Data **Information**. If further information is needed, contact Rugged Coatings Technical Service at 205-440-4996.